



- **Reliable Performance**
- **Integrated 3G/LTE Cellular**
- **Truly Industrial**
- **Field Protocol Support**
- **Cloud Certified**
- **Open Platform**
- **Customizable**



Features

Reliable Performance - Powerful and efficient: single, dual and quad core Intel Atom E3800, soldered-down eMMC storage and ECC memory for additional protection

Integrated Cellular - Certified 3G/LTE cellular modems can be integrated. It also supports Eurotech ReliaCELL 10-20, the cellular module with global carrier precertifications

Truly Industrial - Extended operating temperature, a wide range power supply with surge and sag protection, isolated and protected DIO, protected USB and serial

Field Protocol Support - Native support for Modbus, S7 and OPC UA, the extensible, secure, and platform-independent industrial interoperability standard

Cloud Certified - Seamless integration with Eurotech Everyware Cloud, Microsoft Azure, Amazon Web Services IoT and other Cloud services

Open Platform - Provides a Java/OSGi gateway middleware, to free the developer from proprietary solutions

Customizable - Flexible: personalization and full customization options are available, ranging from branding ("skin" and color) to deep HW/SW configurations

Description

The ReliaGATE 20-25 is a high-performance, globally certified, Multi-service IoT Edge Gateway for industrial and lightly rugged applications.

It features up to four cores, soldered-down ECC RAM and storage, extended operating temperature support, wide range power supply, isolated and protected I/O interfaces, and customizable connectivity options.

The ReliaGATE 20-25 configuration options include GPS and LTE connectivity, both integrated and through the ReliaCELL 10-20 family of 2G/3G/LTE external modems with global carrier precertifications.

The ReliaGATE 20-25 comes with Everyware Software Framework (ESF), a commercial, enterprise-ready edition of Eclipse Kura, the open source Java/ OSGi middleware for IoT Edge Gateways.

Distributed and supported by Eurotech, ESF adds advanced security, diagnostics, provisioning and remote access. It supports ready-to-use field protocols (including Modbus, OPC-UA, S7), MQTT connectivity, web-based visual data flow programming and deep configuration.

ESF is also integrated with Everyware Cloud (EC), Eurotech's IoT Integration Platform (separately available), enabling advanced diagnostics, provisioning, and full remote device access and management.

The ReliaGATE 20-25 is Microsoft Azure certified and can also be integrated with 3rd party cloud services such as Amazon Web Services IoT.

Used stand-alone, or in conjunction with EC, the ReliaGATE 20-25 provides a fast go-to-market solution for projects of any size.

Ordering code: REGATE-20-25-**XX**

HARDWARE CONFIGURATION		- XX1	- XX2	- XX3	- XX4	- XX5	- XX8	
PROCESSOR	CPU	E3815, 1.46GHz, Single Core	E3827, 1.75GHz, Dual Core		E3845, 1.91GHz, Quad Core			
MEMORY	RAM	2GB, 1067MHz (DDR3L-ECC)	2GB, 1333MHz (DDR3L-ECC)		4GB, 1333MHz (DDR3L-ECC)			
STORAGE	Embedded	8GB eMMC						
	SATA	1x SATA 2.0 (Internal Connector) – 1x 32GB mSATA (Included on - XX4 Variants)						
	Other	1x microSD Slot (User Accessible)						
I/O INTERFACES	Ethernet	2x 10/100/1000Mbps - RJ45						
	USB	1x Host 3.0, 1x Host 2.0, 1x ReliaCELL (Noise and Surge Protected) - Type A						
	Serial	2x RS-232/RS-422/RS-485 (9 Wires, Noise and Surge Protected) on DB9 – 1x Serial Console TTL						
	CAN 2.0B	1x CAN bus with 5V (100mA) Power Out						
	Digital I/O	3x Digital Input 7 - 35VDC, 1KV Optoisolated – 3x Digital Output (40VDC), 20mA Sink						
	Video	1x Mini DisplayPort						
	Audio	Factory Option						
EXPANSION	miniPCIe Slots	Up to 3x Full/Half Size Mini PCIe (PCIe/USB/mSATA)						
RADIO INTERFACES	Cellular	Eurotech ReliaCELL 10-20					LTE Cat 4 (EU) 2G/3G Fallback	
	GPS	Eurotech ReliaCELL 10-20 – Factory Option: Integrated GPS						
	Wi-Fi / BT	No	b/g/n, BLE		No	b/g/n, BLE		
OTHER	RTC	Yes (User Accessible Battery)						
	Ext. Watchdog	Yes						
	Sensors	Temperature, Accelerometer						
	LEDs	1x Power, 3x miniPCIe Slot, 2x Programmable (Dual Color Green/Amber)						
	Buttons	1x Reset, 1x Programmable						
POWER	Input	7 - 35VDC (Nominal 12VDC), Surge and Sag Protection, Vehicle Ignition Input						
	Consumption	7W Idle	10W Idle		12W Idle			
ENVIRONMENT	Operating Temp	- 20 to +60°C	- 40 to +65°C					
	Storage Temp	- 40 to +85°C						
CERTIFICATIONS	Regulatory	CE, FCC, ISED						
	Safety	EN 62368, UL 60950 (§)						
	Environmental	RoHS2, REACH						
	Wi-Fi / BT Radio	RED, FCC					RED	
	Cellular Radio	Eurotech ReliaCELL 10-20 Carrier Certifications					RED	
	IoT Platform	Microsoft Azure Certified						
	Ingress	IP40						
MECHANICAL	Enclosure	Material: Anodized Aluminium - Color: Aluminum						
	Dimensions	192x131x52mm (WxDxH)						

Ordering code: REGATE-20-25-**XX**

CONFIGURATION		- XX3	- XX4
SOFTWARE	OS	Yocto Linux	Windows 10 IoT Enterprise
	SDK	Yocto-based Eclipse Tooling, Oracle Java SE	-
	IoT Framework	Everyware Software Framework (Java/OSGi)	-

(§) UL, NRTL listing Factory Option.

Note: The information in this document is subject to change without notice and should not be construed as a commitment by EUROTECH. While reasonable precautions have been taken, EUROTECH assumes no responsibility for any error that may appear in this document. All trademarks or registered trademarks are the properties of their respective companies.